

Industrial/Commercial Application
Heavy Cart to Medium Motorized Traffic



Picture shown is Model 9100V it has an optional 14" x 16" vision panel and 18" high teardrop bumpers.

DOUBLE ACTING "INSULATED" TRAFFIC DOOR

- **INSULATED DOORS WITH INTERNAL STRUCTURAL ALUMINUM FRAMING**
- **IDEAL FOR MEDIUM MOTORIZED TRAFFIC IN AREAS WHERE TEMPERATURE CONTROL IS REQUIRED**
- **DOORS ARE USDA ACCEPTED**

NATIONAL ACCESS DESIGN, LLC doors are available in single or double panel.

FEATURES:

- Doors are constructed with welded aluminum framing, insulated with expanded polystyrene. Overall thickness 1".
- Hinges are V-CAM assembly with 10" jamb guard for Model 9100V or GS style rollers with bottom pin for Model 9100.
- Standard windows are 9" x 14" x 1/4" acrylic set in low profile, high strength sealed plastic frames.
- Available standard colors are black, canyon blue, green, brown, white, beige, dark gray, light gray and red.
- Doors can be manufactured to fit up to an 8' x 10' bi-parting or 4' x 10' single panel opening. *Consult factory for larger openings.*
- Washdown package available.

National Access Design, LLC

phone: 513-351-3400 • fax: 866-300-4539


sales@nationalaccessdesign.com • 1924 Losantiville Avenue • Cincinnati, Ohio 45237

ARCHITECTURAL SPECIFICATIONS

Where indicated on plans, furnish model 9100 double acting, gravity actuated traffic door as manufactured by National Access Design LLC, Cincinnati, Ohio. Doors shall be constructed with welded aluminum framing and expanded polystyrene insulation. Overall thickness will be 1". Windows to be 9" x 14" x 1/4" acrylic set in low profile plastic frames. Facing to be ABS high impact plastic. Doors to be fully gasketed. Hardware to be GS style hinge with cam plate, rollers and bottom pin assembly, or V-CAM with 10" jamb guard. To fit door opening size:

_____ width x _____ height

- Single Bi-Parting



OPTIONS:

Abuse plates, jamb guards, scuff plates, and bumper strips are available as an upgrade.

TEARDROP BUMPERS (BOTH SIDES)

- FB12 (12") FB18 (18") FB24 (24")
 FB30 (30") FB36 (36") FB42 (42")
 FB48 (48")

IMPACT PLATES (BOTH SIDES)

- PL12 (12") PL18 (24") PL24 (24")
 PL30" (30") PL 36 (36") PL42 (42")
 PL48 (48")

STAINLESS STEEL

- SS12 (12") SS18 (18") SS24 (24")
 SS30 (30") SS36 (36") SS42 (42")
 SS48 (48")

WINDOWS

- 6" x 12" (Double Pane Only) 22" x 22"
 9" x 14" (STND) 10" x 30"
 14" x 16"

JAMB GUARD OPTIONS

- Bottom Pin (STND) w/GS Hinge
 JG 10" (STND) w/V-CAM Hinge
 Stainless Steel Hinge Option

FACING

- ABS (STND)
 Stainless Steel

DOOR FRAMES

- Tube Style - Primed Steel
 Tube Style - Stainless Steel
 C-Channel - Primed Steel
 C-Channel - Stainless Steel

OTHER

- Cane Bolts
 Locking Sleeve
 Limiting Posts
 Rub Rails / Cart Guards
 Urethane Insulation Upgrade



Model 9100 or Model 9100V Traffic Doors are shipped FOB Factory.

Customer: _____

Approved By: _____ Date: _____