

MODEL 9100 OR 9100V FULLY GASKETED

Industrial • Commercial Application Heavy Cart to Medium Motorized Traffic



Picture shown is Model 9100V it has optional 18" high teardrop bumpers.

DOUBLE ACTING "INSULATED" TRAFFIC DOOR

- INSULATED DOORS WITH INTERNAL STRUCTURAL ALUMINUM FRAMING
- IDEAL FOR MEDIUM MOTORIZED
 TRAFFIC IN AREAS WHERE
 TEMPERATURE CONTROL IS REQUIRED
- DOORS ARE USDA ACCEPTED





NATIONAL ACCESS DESIGN, LLC doors are available in single or double panel.

FEATURES:

- Doors are constructed with welded aluminum framing, insulated with expanded polystyrene.
 Overall thickness 1".
- Hinges are V-CAM assembly with 10" jamb guard for Model 9100V or GS style rollers with 10" jamb guards for Model 9100.
- Standard windows are 9" x 14" x 1/4" acrylic set in low profile, high strength sealed plastic frames.
- Available standard colors are black, canyon blue, green, brown, white, beige, dark gray, light gray and red.
- Doors can be manufactured to fit up to an 10'x10' bi-parting or 5'x10' single panel opening.
 Consult factory for larger openings.
- Washdown package available.

National Access Design, LLC

phone: 513-351-3400 • fax: 866-300-4539

sales@nationalaccessdesign.com • 1924 Losantiville Avenue • Cincinnati, Ohio 45237

ARCHITECTURAL SPECIFICATIONS

Where indicated on plans, furnish model 9100 double acting, gravity actuated traffic door as manufactured by National Access Design LLC, Cincinnati, Ohio. Doors shall be constructed with welded aluminum framing and expanded polystyrene insulation. Overall thickness will be 1". Windows to be 9" x 14" x 1/4" acrylic set in low profile plastic frames. Facing to be ABS high impact plastic. Doors to have full perimeter gasket. Hinges are V-CAM assembly with 10" jamb guard for Model 9100V or GS style rollers with 10" jamb guards for Model 9100.

9° 14"	GS-HINGE ASSEMBLY - 9100 OR V-C AM V-C AM SSEMBLY - 9100V
Optional TEARDROP BUMPER	STRUCTURAL ALUMINUM W/ FOAM CORE

To fit door opening size:

 width x_	 height
Single	Bi-Parting

OPTIONS:

Teardrop Bumpers and Impact plates are available as an upgrade. 10" Jamb Guards (STND).	HINGE OPTIONS ☐ GS Hinge = 9100 ☐ V-CAM = 9100V		
TEARDROP BUMPERS (BOTH SIDES) ☐ FB12 (12") ☐ FB18 (18") ☐ FB24 (24") ☐ FB30 (30") ☐ FB 36 (36") ☐ FB42 (42") ☐ FB48 (48")	THERMOPLASTIC FACINGS COLOR OPTIONS BLACK WHITE BROWN GREEN LT. GRAY CANYON BLUE		
IMPACT PLATES (BOTH SIDES) BLACK ABS (STANDARD) □ PL12 (12") □ PL18 (18") □ PL24 (24") □ PL30 (30") □ FB36 (36") □ PL42 (42") □ FB48 (48")	DOOR FRAMES ☐ Tube Style - Powder Coated Steel ☐ Tube Style - Stainless Steel ☐ C-Channel - Powder Coated Steel ☐ C-Channel - Stainless Steel		
STAINLESS STEEL □ SS12 (12") □ SS18 (18") □ SS24 (24") □ SS30 (30") □ SS36 (36") □ SS42 (42") □ SS48 (48") WINDOWS □ 9" x 14" (STND) □ 10" x 30" □ 14" x 16" □ 22" x 22"	OPTIONS Limiting Posts Rub Rails Locking Collars Stainless Steel Hardware Upgrade SS Jamb Guard - JG 10" Transom Panels For Openings Over 10" High		



Model 9100 or Model 9100V Traffic Doors are shipped FOB Factory.

Customer: ______ Date: ______